

74F273 Octal D Flip-Flop

General Description

The 'F273 has eight edge-triggered D-type flip-flops with individual D inputs and Q outputs. The common buffered Clock (CP) and Master Reset (MR) inputs load and reset (clear) all flip-flops simultaneously.

The register is fully edge-triggered. The state of each D input, one setup time before the LOW-to-HIGH clock transition, is transferred to the corresponding flip-flop's Q output.

All outputs will be forced LOW independently of Clock or Data inputs by a LOW voltage level on the MR input. The device is useful for applications where the true output only is required and the Clock and Master Reset are common to all storage elements.

Features

- Ideal buffer for MOS microprocessor or memory
- Eight edge-triggered D flip-flops
- Buffered common clock
- Buffered, asynchronous Master Reset
- See 'F377 for clock enable version
- See 'F373 for transparent latch version
- See 'F374 for 3-STATE version
- Guaranteed 4000V minimum ESD protection



Ordering Code:

Commercial	Military	Package Number	Package Description
74F273PC		N20A	20-Lead (0.300" Wide) Molded Dual-In-Line
	54F273DM (Note 2)	J20A	20-Lead Ceramic Dual-In-Line
74F273SC (Note 1)		M20B	20-Lead (0.300" Wide) Molded Small Outline, JEDEC
74F273SJ (Note 1)		M20D	20-Lead (0.300" Wide) Molded Small Outline, EIAJ
	54F273FM (Note 2)	W20A	20-Lead Cerpack
	54F273LM (Note 2)	E20A	20-Lead Ceramic Leadless Chip Carrier, Type C

Note 1: Devices also available in 13" reel. Use suffix = SCX and SJX.


Note 2: Military grade device with environmental and burn-in processing. Use suffix = DMQB, FMQB and LMQB.

Logic Symbols




Connection Diagrams

Pin Assignment for
DIP, SOIC and Flatpak



DS009511-1

Pin Assignment
for LCC



DS009511-2

Unit Loading/Fan Out


Pin Names	Description	54F74F	
		U.L. HIGH/LOW	Input I_{IH}/I_{IL} Output I_{OH}/I_{OL}
D_0-D_7	Data Inputs	1.0/1.0	20 μA / -0.6 mA
\overline{MR}	Master Reset (Active LOW)	1.0/1.0	20 μA / -0.6 mA
CP	Clock Pulse Input (Active Rising Edge)	1.0/1.0	20 μA / -0.6 mA
Q_0-Q_7	Data Outputs	50/33.3	-1 mA / 20 mA

Mode Select-Function Table

Operating Mode	Inputs			Output
	\overline{MR}	CP	D_n	Q_n
Reset (Clear)	L	X	X	L
Load "1"	H	↗	h	H
Load "0"	H	↗	l	L

H = HIGH Voltage Level steady state
h = HIGH Voltage Level one setup time prior to the LOW-to-HIGH clock transition
L = LOW Voltage Level steady state
l = LOW Voltage Level one setup time prior to the LOW-to-HIGH clock transition
X = Immaterial
↗ = LOW-to-HIGH clock transition

Logic Diagram



DS009511-4

Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Absolute Maximum Ratings (Note 3)

Storage Temperature	-65°C to +150°C
Ambient Temperature under Bias	-55°C to +125°C
Junction Temperature under Bias	-55°C to +175°C
Plastic	-55°C to +150°C
V _{CC} Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 4)	-0.5V to +7.0V
Input Current (Note 4)	-30 mA to +5.0 mA
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	
Standard Output	-0.5V to V _{CC}
3-STATE Output	-0.5V to +5.5V
Current Applied to Output in LOW State (Max)	twice the rated I _{OL} (mA)

ESD Last Passing Voltage (min)

4000V


Recommended Operating Conditions

Free Air Ambient Temperature	
Military	-55°C to +125°C
Commercial	0°C to +70°C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

Note 3: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 4: Either voltage limit or current limit is sufficient to protect inputs.

DC Electrical Characteristics

Symbol	Parameter	54F/74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage			0.8	V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage			-1.2	V	Min	I _{IN} = -18 mA
V _{OH}	Output HIGH Voltage	Mil	2.5		V	Min	I _{OH} = -1 mA
		10% V _{CC}	2.5				
		5% V _{CC}	2.7				
V _{OL}	Output LOW Voltage	Mil		0.5	V	Min	I _{OL} = 20 mA
		10% V _{CC}		0.5			
		5% V _{CC}		0.5			
I _{IH}	Input HIGH Current	54F		20.0	μA	Max	V _{IN} = 2.7V
		74F		5.0			
I _{BVI}	Input HIGH Current Breakdown Test	54F		100	μA	Max	V _{IN} = 7.0V
		74F		7.0			
I _{CEX}	Output HIGH Leakage Current	54F		250	μA	Max	V _{OUT} = V _{CC}
		74F		50			
V _{ID}	Input Leakage Test	74F	4.75		V	0.0	I _{ID} = 1.9 μA All other pins grounded
I _{OD}	Output Leakage Circuit Current	74F		3.75	μA	0.0	V _{IOD} = 150 mV All other pins grounded
I _{IL}	Input LOW Current			-0.6	mA	Max	V _{IN} = 0.5V
I _{OS}	Output Short-Circuit Current			-60	-150	mA	Max V _{OUT} = 0V
I _{CCH}	Power Supply Current			44	mA	Max	CP = 
I _{CCL}				56	mA	Max	D _n = \overline{MR} = HIGH

AC Electrical Characteristics


Symbol	Parameter	74F		54F		74F		Units
		$T_A = +25^\circ\text{C}$ $V_{CC} = +5.0\text{V}$ $C_L = 50\text{ pF}$		$T_A, V_{CC} = \text{Mil}$ $C_L = 50\text{ pF}$		$T_A, V_{CC} = \text{Com}$ $C_L = 50\text{ pF}$		
		Min	Typ	Max	Min	Max	Min	
f_{max}	Maximum Clock Frequency	160		95		130		MHz
t_{PLH}	Propagation Delay	3.0	7.0	2.5	9.5	2.5	7.5	ns
t_{PHL}	Clock to Output	4.0	9.00	3.0	11.0	3.5	9.0	
t_{PLH}	Propagation Delay	4.5	9.5	3.0	11.0	4.0	10.0	ns
t_{PHL}	MR to Output							

AC Operating Requirements

Symbol	Parameter	74F		54F		74F		Units
		$T_A = +25^\circ\text{C}$ $V_{CC} = +5.0\text{V}$		$T_A, V_{CC} = \text{Mil}$		$T_A, V_{CC} = \text{Com}$		
		Min	Max	Min	Max	Min	Max	
$t_{\text{s}}(\text{H})$	Setup Time, HIGH or LOW	3.0		3.5		3.0		ns
$t_{\text{s}}(\text{L})$	Data to CP	3.5		4.0		3.5		
$t_{\text{h}}(\text{H})$	Hold Time, HIGH or LOW	0.5		1.0		0.5		ns
$t_{\text{h}}(\text{L})$	Data to CP	1.0		1.0		1.0		
$t_{\text{w}}(\text{L})$	$\overline{\text{MR}}$ Pulse Width, LOW	6.0		4.0		6.0		ns
$t_{\text{w}}(\text{H})$	CP Pulse Width	6.0		5.0		6.0		ns
$t_{\text{w}}(\text{L})$	HIGH or LOW	6.0		5.0		6.0		
t_{rec}	Recovery Time, $\overline{\text{MR}}$ to CP	3.0		4.5		3.5		ns


Ordering Information

The device number is used to form part of a simplified purchasing code where a package type and temperature range are defined as follows:



DS009511-6


Physical Dimensions inches (millimeters) unless otherwise noted




E20A (REV D)

**20-Lead Ceramic Leadless Chip Carrier (LCC)
Package Number E20A**

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




20-Lead Ceramic Dual-In-Line Package (D)
Package Number J20A




20-Lead (0.300" Wide) Molded Small Outline Package, JEDEC (S)
Package Number M20B

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




Lit. # 114645



20-Lead (0.300" Wide) Molded Dual-In-Line Package (P)
Package Number N20A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



**20-Lead Ceramic Flatpak (F)
Package Number W20A**

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Fairchild Semiconductor Corporation Americas
Customer Response Center
Tel: 1-888-522-5372

Fairchild Semiconductor Europe
Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 8 141-35-0
English Tel: +44 (0) 1 793-85-68-56
Italy Tel: +39 (0) 2 57 5631

Fairchild Semiconductor Hong Kong Ltd.
13th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: +852 2737-7200
Fax: +852 2314-0061

National Semiconductor Japan Ltd.
Tel: 81-3-5620-6175
Fax: 81-3-5620-6179

www.fairchildsemi.com